Application No.: 10/579,952 2 Docket No.: 220002067500

AMENDMENTS TO THE CLAIMS

Claims 1-4. (canceled)

5. (currently amended): A kit comprising

a self-contained cell culture vessel comprising a cell reservoir, a media reservoir, and a gas reservoir;

cells and a cryoprotectant containing medium disposed in said cell reservoir;

a liquid cell culture medium disposed in said media reservoir in an amount capable of diluting the cryoprotectant to a volume suitable for cell growth, wherein thawing of the cryoprotectant containing medium and the liquid cell culture medium combines the cells, the cryoprotectant containing medium, and the liquid cell culture medium to provide a medium to culture the cells; and

gas disposed in the gas reservoir.

- 6. (previously presented): The kit of claim 5 maintained at a subzero temperature.
- 7. (previously presented): The kit of claim 5, further comprising an internal chamber.
- 8. (previously presented): The kit of claim 7, wherein

the internal chamber defines a space therein and has an internal surface;

the internal chamber defines at least one optionally sealable port or channel;

the internal chamber defines at least one sealable opening for receiving a gas reservoir capable of fluid communication with the internal chamber;

wherein the gas reservoir contains a valve or removable seal;

wherein the cell reservoir is capable of fluid communication with the internal chamber and defines an optional valve or seal therebetween;

wherein the media reservoir is capable of fluid communication with the internal chamber and defines an optional valve or seal therebetween;

wherein the vessel is capable of being sealed; and

wherein the vessel is made from a material capable of withstanding subzero temperatures without degrading.

Application No.: 10/579,952 3 Docket No.: 220002067500

9. (previously presented): The kit of claim 8 wherein the vessel further comprises a liquid impermeable flexible partition having two sides displaced within the internal chamber, the two sides defining a first and a second space within the internal chamber;

wherein the partition is capable of exchanging gas between said first and second space; wherein the first space is capable of containing a liquid in communication with at least one port or channel, and defines a sealable access port, and

wherein the first space is capable of fluid communication with the cell reservoir and/or the media reservoir;

wherein the second space is capable of containing a gas, and said second space is capable of fluid communication with the gas reservoir; and

wherein the edges of the partition are sealed to a portion of the internal surface of the internal chamber to prevent liquid communication between said spaces.

10. (previously presented): The kit of claim 9, wherein the second space for containing a gas is further defined by

a fluid and gas impermeable expandable wall affixed to a rigid wall of the internal chamber and forming an integral portion of the internal chamber.

11. (previously presented): The kit of claim 8

wherein one or more of the valves or seals is capable of opening and closing;

wherein at least one port or channel sealably connects to at least one additional media chamber through at least one fluid channel, wherein at least one valve or seal is displaced between each port or channel and each media chamber; and wherein the media chamber is located externally to the vessel;

wherein at least one port or channel sealably connects to at least one absorbent chamber, wherein at least one valve or seal is displaced between each additional port or channel and the absorbent chamber; and

further comprising a cell filter between each valve or seal and each absorbent chamber.

12. (previously presented): The kit of claim 7, wherein the gas reservoir is a self-contained capsule disposed within the internal chamber.

Application No.: 10/579,952 4 Docket No.: 220002067500

13. (previously presented): The kit of claim 7,

wherein the gas reservoir is disposed outside the internal chamber, and is sealably connected to the internal chamber.

- 14. (previously presented): The kit of claim 7, wherein the cell reservoir and the media reservoir are contained within the internal chamber.
- 15. (previously presented): The kit of claim 7, wherein the cell reservoir and/or the media reservoir is a self-contained capsule.
- 16. (previously presented): The kit of claim 8,

wherein the seal or valve defined between the gas reservoir and the internal chamber is selected from the group consisting of a) a temperature or electrically sensitive seal; b) a diaphragm adapted to be penetrated, or c) a mechanically, thermally or electrically operated valve.

- 17. (previously presented): The kit of claim 16, comprising a temperature sensitive seal and further comprising a safety seal.
- 18. (previously presented): The kit of claim 8, wherein the internal chamber is removably or fixedly connected to at least one measuring device via at least one port or channel.
- 19. (previously presented): The kit of claim 18, wherein the measuring device is a Micro Electro Mechanical System (MEMS) and/or high performance liquid chromatograph (HPLC).
- 20. (previously presented): The kit of claim 18, wherein a port or channel defines a mechanism to provide fluid communication between the internal chamber and the measuring device.
 - 21. (previously presented): The kit of claim 20, wherein the mechanism is a ball valve or a perforable diaphragm.

Application No.: 10/579,952 5 Docket No.: 220002067500

- 22. (previously presented): The kit of claim 8, wherein the internal chamber defines one or two ports or channels.
- 23. (previously presented): The kit of claim 21, wherein the measuring device further comprises a member for operating the ball valve or for penetrating the diaphragm.
 - 24. (previously presented): The kit of claim 18, further comprising a filter within the port or channel for preventing contamination in the internal chamber.
 - 25. (previously presented): The kit of claim 8, wherein the sealable access port is removably sealed with an access port closure.
- 26. (previously presented): The kit of claim 8, further comprising at least one sensor externally connected to at least one port or channel or disposed inside the internal chamber.
 - 27. (previously presented): The kit of claim 26, wherein the sensor senses oxygen, CO₂, or pH levels.
 - 28-30. (canceled)